



**PACKING DIMENSIONS**

DIAMETER: 1050mm  
 STANDARD TOTAL HEIGHT: 4300mm  
 STANDARD TOTAL WEIGHT: 419kg's

TOTAL HEIGHT MAY VARY WITH  
 INSTALLATION SITE SOIL CONDITIONS  
 AND ENGINEERING REQUIREMENTS.

LOGITUDINAL STEEL REINFORCING  
 BAR SIZE AND LIGATURE SIZE  
 WILL BE IN ACCORDANCE WITH  
 ENGINEERING REQUIREMENTS.

**STANDARDS**  
 ALL PRODUCTS TO CONFORM TO THE FOLLOWING AUSTRALIAN STANDARDS

- \* AS 1170.2: Structural design actions – Wind actions.
- \* AS 1302: Geometrical pro I
- \* AS 3678: Concrete structures.
- \* AS 3678: Structural steel – Hot rolled plates, floorplates and slabs.
- \* AS 4680: Hot dip galvanized (Zinc) Coatings on fabricated ferrous articles.
- \* AS/NZS 4671: Steel reinforcing materials.
- \* AS/NZS 4600: Cold formed steel structures.
- \* AS/NZS 4676: Structural design requirements for utility services poles.



G&S Industries

97 GUTHRIE STREET, OSBORNE PARK W.A. 6017  
 PH (08) 9446 8044. (08) 9446 8266  
 FAX (08) 9446 5456

JOB NO.	DATE:	DESIGN:	DRAWN:
36MM CAGED RAGBOLT ASSEMBLY FULLY WELDED AND ASSEMBLED 890634 CR36/16/860		S.G.	Z.L.
		CHECKED:	APPROVED:
		R.G.	Y
		LAST REVISED:	SCALE:
		13 MAR '10	NTS
		DRAWING:	REVISION:
		ZLRG2398	03