



PACKING DIMENSIONS

DIAMETER: 1050mm
 STANDARD TOTAL HEIGHT: 4300mm
 STANDARD TOTAL WEIGHT: 358kg's

TOTAL HEIGHT MAY VARY WITH
 INSTALLATION SITE SOIL CONDITIONS
 AND ENGINEERING REQUIREMENTS.

LOGITUDINAL STEEL REINFORCING
 BAR SIZE AND LIGATURE SIZE
 WILL BE IN ACCORDANCE WITH
 ENGINEERING REQUIREMENTS.

STANDARDS

- ALL PRODUCTS TO CONFORM TO THE FOLLOWING AUSTRALIAN STANDARDS
- * AS 1170.2: Structural design actions – Wind actions.
 - * AS 1302: Geometrical product specifications Indication of surface texture in technical production documentation.
 - * AS 1554(see) Structural steel welding set.
 - * AS 2159: Piling – Design & installation.
 - * AS 2870: Residential slab footings – Construction.
 - * AS 3600: Concrete structures.
 - * AS 3678: Structural steel – Hot rolled plates, floorplates and slabs.
 - * AS 4680: Hot dip galvanized (Zinc) Coatings on fabricated ferrous articles.
 - * AS/NZS 4671: Steel reinforcing materials.
 - * AS/NZS 4600: Cold formed steel structures.
 - * AS/NZS 4676: Structural design requirements for utility services poles.



G&S Industries

97 GUTHRIE STREET, OSBORNE PARK W.A. 6017
 PH (08) 9446 8044. (08) 9446 8266
 FAX (08) 9446 5456

JOB NO.

DATE:

DESIGN:

DRAWN:

S.G.

Z.L.

CHECKED:

APPROVED:

R.G.

Y

LAST REVISED:

SCALE:

13 MAR '10

NTS

DRAWING:

REVISION:

ZLRG2397

03