



PACKING DIMENSIONS

DIAMETER: 1050mm
 STANDARD TOTAL HEIGHT: 4300mm
 STANDARD TOTAL WEIGHT: 419kg's

TOTAL HEIGHT MAY VARY WITH
 INSTALLATION SITE SOIL CONDITIONS
 AND ENGINEERING REQUIREMENTS.

LOGITUDINAL STEEL REINFORCING
 BAR SIZE AND LIGATURE SIZE
 WILL BE IN ACCORDANCE WITH
 ENGINEERING REQUIREMENTS.

STANDARDS
 ALL PRODUCTS TO CONFORM TO THE FOLLOWING AUSTRALIAN STANDARDS

- * AS 1170.2: Structural design actions – Wind actions.
- * AS 1302: Geometrical pro I
- * AS 3678: Concrete structures.
- * AS 3678: Structural steel – Hot rolled plates, floorplates and slabs.
- * AS 4680: Hot dip galvanized (Zinc) Coatings on fabricated ferrous articles.
- * AS/NZS 4671: Steel reinforcing materials.
- * AS/NZS 4600: Cold formed steel structures.
- * AS/NZS 4676: Structural design requirements for utility services poles.



G&S Industries

97 GUTHRIE STREET, OSBORNE PARK W.A. 6017
 PH (08) 9446 8044. (08) 9446 8266
 FAX (08) 9446 5456

JOB NO.	DATE:	DESIGN:	DRAWN:
36MM CAGED RAGBOLT ASSEMBLY FULLY WELDED AND ASSEMBLED 890634 CR36/16/860		S.G.	Z.L.
		CHECKED:	APPROVED:
		R.G.	Y
		LAST REVISED:	SCALE:
		13 MAR '10	NTS
		DRAWING:	REVISION:
		ZLRG2398	03