

4 x M20 OR M24 FERRULES @ 350
PCD TO SUIT M20 OR M24
THREADED ROD BOLTS
(SUPPLIED)

4 x R30CB - GRADE 8.8 ANCHOR BOLT
ARRANGEMENTS @ 466MM PCD
(AS PER ZLRG4161A)

ELECTRICAL
CONDUITS

1200

1200

230 TYP

230 TYP

800

FEMALE COUPLING
FITTED TO CONDUIT
(BOTH SIDES)

REID SWIFTLIFTS ANCHORS
IN EACH CORNER

CONCRETE BASE

FORKLIFT SLEEVES

3D VIEW

SCALE 1:20

NOTE :

- PRECAST SLAB CAN BE INSTALLED ABOVE GROUND OR BURIED
- PLEASE FOLLOW G&S PROCEDURE "GPS 17" FOR GROUND PREPARATION.
(AVAILABLE ON APPLICATION)

STANDARDS

ALL PRODUCTS TO CONFORM TO THE FOLLOWING AUSTRALIAN STANDARDS.

- * AS 1170.2 Structural design actions - Wind actions.
- * AS 1554(set) Structural steel welding set.
- * AS 2159: Piling - Design & Installation.
- * AS 2870: Residential slab footings - Construction.
- * AS 3600: Concrete structures
- * AS 3678: Structural steel - Hot rolled plates, floorplates and slabs.
- * AS 4680: Hot dip galvanized (Zinc) Coatings on fabricated ferrous articles.
- * AS/NZS 4671: Steel reinforcing materials.
- * AS/NZS 4600: Cold formed steel structures.



97 GUTHRIE STREET,
OSBORNE PARK W.A. 6017
PH : +6108 9446 8044
EMAIL: sales@gsindustries.com.au
WEB: www.gsindustries.com.au

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY
OF G&S INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF G&S INDUSTRIES IS PROHIBITED.

SCALE: AS SHOWN

PRODUCT WEIGHT: 2646kg.

PRODUCT FINISH:
CONCRETE FINISH OR PAINTED

CUSTOMER APPROVAL:

CUSTOMER NAME / PROJECT:

	NAME	DATE
DRAWN	N. A.	21.07.2025
CHECKED	S. G.	21.07.2025
APPROVED	R. G.	21.07.2025

COPYRIGHT

THIS DOCUMENT IS PRODUCED BY G&S INDUSTRIES
MUST NOT BE COPIED, TRACED, REPRODUCED,
OR LENT WITHOUT WRITTEN CONSENT

PART NUMBER :

CB1.2-0.8

TITLE :

**1200 x 1200 x 800mm
PRECAST CONCRETE BASE
C/W FORK SLEEVES & LIFTING POINTS**

SIZE DWG. NO.

A4

ZLRG4464

REV.

3

SHEET 1 OF 1